



SLOGGING SPANNERS

"POWERFUL"

► Top-grade industrial quality for the hardest of continuous use



 mm	 "AF
27 – 170	1" – 4"

133 (MM)

OPEN ENDED SLOGGING SPANNER



- For very heavy-duty work
- Acc. to DIN 133
- Up to length 500 mm chrome-vanadium steel 31CrV3, above 525 mm material C35
- Special sizes available on request
- * not standardised



 mm *	L	a	b		Code	No.
27	181	16.3	56.0	0.385	6410570	133 27
30	188	16.7	62.0	0.451	6400260	133 30
32	196	17.2	66.0	0.552	6400340	133 32
34	196	17.2	66.0	0.559	6411030	133 34
36	211	18.2	76.0	0.709	6400420	133 36
41	227	19.2	88.0	1.000	6400500	133 41
46	256	19.7	98.0	1.258	6400690	133 46
50	281	21.2	106.5	1.609	6400770	133 50
55	310	23.6	117.0	2.131	6400850	133 55
60	321	24.1	128.0	2.484	6400930	133 60
65	351	27.6	139.0	3.340	6401070	133 65
70	370	29.6	150.0	4.325	6401150	133 70
75	390	31.0	161.5	5.110	6401230	133 75
80	406	34.0	172.5	6.020	6401310	133 80
85	406	34.0	172.5	5.770	6401580	133 85
90	456	38.4	194.0	8.905	6401660	133 90
95	456	38.4	194.0	8.985	6401740	133 95
100	500	46.3	225.5	13.315	6401820	133 100
105	500	46.3	225.5	13.220	6401900	133 105
110	500	46.3	225.5	13.045	6402040	133 110
115	525	54.2	245.5	17.660	6402120	133 115
120	525	54.2	245.5	17.610	6402200	133 120
125 *	545	50.0	255.0	16.760	6402390	133 125
130	575	55.0	275.0	19.030	6402470	133 130
135	575	55.0	275.0	18.880	6402550	133 135
140 *	575	55.0	275.0	17.880	6402630	133 140
145	640	60.0	305.0	26.665	6402710	133 145
150	640	60.0	305.0	24.660	6402980	133 150
160 *	640	60.0	305.0	25.690	6403280	133 160
165	715	70.0	342.0	39.560	6403360	133 165
170	715	70.0	342.0	37.760	6403440	133 170

133 (AF)

OPEN ENDED SLOGGING SPANNER




- For very heavy-duty work
- Up to length 500 mm chrome-vanadium steel 31CrV3, above 525 mm material C35
- Special sizes available on request



 "AF	L	a	b		Code	No.
1	181	16.3	56.0	0.392	6403950	133 1AF
1.1/16	181	16.3	56.0	0.392	6404090	133 1.1/16AF
1.1/8	181	16.3	56.0	0.394	6404170	133 1.1/8AF
1.3/16	188	16.7	62.0	0.470	6404250	133 1.3/16AF
1.1/4	188	16.7	62.0	0.461	6404330	133 1.1/4AF
1.5/16	196	17.2	66.0	0.544	6404410	133 1.5/16AF
1.3/8	196	17.2	66.0	0.547	6404680	133 1.3/8AF
1.7/16	211	18.2	76.0	0.713	6404760	133 1.7/16AF
1.1/2	211	18.2	76.0	0.699	6404840	133 1.1/2AF
1.5/8	227	19.2	88.0	0.980	6404920	133 1.5/8AF
1.11/16	227	19.2	88.0	0.981	6405060	133 1.11/16AF
1.3/4	227	19.2	88.0	0.987	6405140	133 1.3/4AF
1.13/16	256	19.7	98.0	1.272	6405220	133 1.13/16AF
1.7/8	256	19.7	98.0	1.271	6405570	133 1.7/8AF
2	281	21.2	106.5	1.594	6405650	133 2AF
2.1/16	281	21.2	106.5	1.640	6405730	133 2.1/16AF
2.1/8	281	21.2	106.5	1.559	6407780	133 2.1/8AF
2.3/16	310	23.6	117.0	2.115	6408160	133 2.3/16AF
2.1/4	310	23.6	117.0	2.095	6408240	133 2.1/4AF
2.3/8	321	23.6	128.0	2.466	6408320	133 2.3/8AF
2.7/16	321	23.6	128.0	2.396	6408400	133 2.7/16AF
2.9/16	351	27.6	139.0	3.490	6408590	133 2.9/16AF
2.5/8	351	27.6	139.0	3.270	6408670	133 2.5/8AF
2.3/4	370	29.6	150.0	4.280	6408750	133 2.3/4AF
3	390	31.0	161.5	4.880	6408830	133 3AF
3.1/8	406	34.0	172.5	5.950	6408910	133 3.1/8AF
3.3/8	406	34.0	172.5	5.640	6409050	133 3.3/8AF
3.1/2	456	38.4	194.0	8.910	6409130	133 3.1/2AF
3.3/4	456	38.4	194.0	8.555	6409210	133 3.3/4AF
3.7/8	500	46.3	225.5	13.465	6409480	133 3.7/8AF
4	500	46.3	225.5	13.635	6409560	133 4AF

**"POWERFUL"**


► Top-grade industrial quality for the hardest of continuous use



mm	"AF"
24 – 175	1" – 4 1/2"

**306 (MM)****RING SLOGGING SPANNER**


- For very heavy-duty work
- Acc. to DIN 7444
- Up to length 435 mm chrome-vanadium steel 31CrV3, above 480 mm from C35
- Special sizes available on request
- * not standardised



mm *	L	a	b		Code	No.
24 *	160	15.0	42.5	0.262	6475000	306 24
27	180	15.5	47.0	0.328	6475190	306 27
30	190	16.5	51.5	0.393	6475270	306 30
32	195	16.5	53.0	0.428	6475350	306 32
34	195	16.5	53.0	0.401	6481670	306 34
36	205	19.5	60.0	0.674	6475430	306 36
38 *	205	19.5	60.0	0.635	6474460	306 38
41	225	20.5	66.0	0.790	6475510	306 41
46	240	22.5	75.0	0.999	6475780	306 46
50	250	23.5	80.0	1.093	6475860	306 50
55	270	25.0	87.5	1.452	6475940	306 55
60	270	26.0	93.5	1.577	6476080	306 60
65	290	29.0	101.0	2.580	6476160	306 65
70	320	32.5	109.5	2.580	6476240	306 70
75	325	34.0	114.5	3.010	6476320	306 75
80	345	35.0	123.0	3.515	6476400	306 80
85	360	37.0	129.0	3.895	6476590	306 85
90	400	41.5	152.0	6.370	6476670	306 90
95	400	41.5	152.0	6.285	6476750	306 95
100	400	41.5	152.0	6.030	6476830	306 100
105	435	47.5	172.0	8.660	6476910	306 105
110	435	47.5	172.0	8.440	6477050	306 110
115	435	47.5	172.0	8.160	6477130	306 115
120	480	54.0	182.0	9.855	6477210	306 120
125 *	480	54.0	182.0	9.665	6477480	306 125
130	520	58.0	202.0	12.295	6477560	306 130
135	520	58.0	202.0	11.790	6477640	306 135
140 *	520	58.0	202.0	11.960	6477720	306 140
145	580	64.0	228.0	18.550	6477800	306 145
150	580	64.0	228.0	17.980	6477990	306 150
155	580	64.0	228.0	16.940	6478020	306 155
160 *	580	64.0	228.0	17.890	6478100	306 160
165	650	70.0	265.0	26.660	6478290	306 165
175 *	650	70.0	265.0	25.920	6478450	306 175

306 (AF)**RING SLOGGING SPANNER**

- For very heavy-duty work
- Up to length 435 mm chrome-vanadium steel 31CrV3, above 480 mm from C35
- Special sizes available on request



"AF"	L	a	b		Code	No.
1	160	15.0	42.5	0.262	6474540	306 1AF
1.1/16	180	15.5	47.0	0.325	6474620	306 1.1/16AF
1.1/8	180	15.5	47.0	0.315	6474700	306 1.1/8AF
1.3/16	190	16.5	51.5	0.389	6474890	306 1.3/16AF
1.1/4	190	16.5	51.5	0.386	6474970	306 1.1/4AF
1.5/16	195	16.5	53.0	0.415	6478530	306 1.5/16AF
1.3/8	195	16.5	53.0	0.409	6478610	306 1.3/8AF
1.7/16	205	19.5	60.0	0.660	6478880	306 1.7/16AF
1.1/2	205	19.5	60.0	0.641	6478960	306 1.1/2AF
1.5/8	225	20.5	66.0	0.820	6479180	306 1.5/8AF
1.11/16	225	20.5	66.0	0.766	6479260	306 1.11/16AF
1.3/4	225	20.5	66.0	0.770	6479340	306 1.3/4AF
1.13/16	240	22.5	75.0	0.982	6479420	306 1.13/16AF
1.7/8	240	22.5	75.0	0.985	6479500	306 1.7/8AF
2	250	23.5	80.0	1.090	6479690	306 2AF
2.1/16	250	23.5	80.0	1.079	6479770	306 2.1/16AF
2.1/8	250	23.5	80.0	1.039	6479850	306 2.1/8AF
2.3/16	270	25.0	87.5	1.431	6479930	306 2.3/16AF
2.1/4	270	25.0	87.5	1.397	6480000	306 2.1/4AF
2.3/8	270	26.0	93.5	1.616	6480190	306 2.3/8AF
2.7/16	270	26.0	93.5	1.531	6480270	306 2.7/16AF
2.9/16	290	29.0	101.0	2.076	6480350	306 2.9/16AF
2.5/8	290	29.0	101.0	2.035	6480430	306 2.5/8AF
2.3/4	320	32.5	109.5	2.545	6480510	306 2.3/4AF
3	325	34.0	114.5	3.005	6480780	306 3AF
3.1/8	345	35.0	123.0	3.365	6480860	306 3.1/8AF
3.3/8	360	36.0	126.0	3.790	6480940	306 3.3/8AF
3.1/2	390	40.0	142.0	5.125	6481080	306 3.1/2AF
3.3/4	400	41.5	152.0	6.130	6481160	306 3.3/4AF
3.7/8	420	45.0	155.0	6.150	6481240	306 3.7/8AF
4.1/2	450	48.0	170.0	7.475	6481590	306 4.1/2AF