


**HOOK SPANNERS**

40

HOOK WRENCH with lug

- Acc. to DIN 1810, Form A
- For slotted round nuts according to DIN 981
- GEDORE vanadium steel 31CrV3, manganese-phosphated




mm	L	b	n	t ₁	kg	Code	No.
16-20	110	2.0	3.8	1.5	0.026	6333990	40 16-20
25-28	135	2.5	4.5	2.0	0.038	6334020	40 25-28
30-32	135	2.5	4.5	2.0	0.043	6334100	40 30-32
34-36	170	3.0	5.5	2.5	0.071	6334290	40 34-36
40-42	170	3.0	5.5	2.5	0.078	6334370	40 40-42
45-50	205	3.5	6.5	3.0	0.133	6334450	40 45-50
52-55	205	3.5	6.5	3.0	0.130	6334530	40 52-55
58-62	240	4.0	7.5	3.5	0.196	6334610	40 58-62
68-75	240	4.0	7.5	3.5	0.208	6334880	40 68-75
80-90	280	5.0	8.5	4.0	0.282	6334960	40 80-90
95-100	280	5.0	8.5	4.0	0.275	6335180	40 95-100
110-115	335	5.0	10.3	4.0	0.491	6335260	40 110-115
120-130	335	5.0	10.3	4.0	0.493	6335340	40 120-130
135-145	385	6.0	12.3	5.0	0.841	6335420	40 135-145
155-165	385	6.0	12.3	5.0	0.820	6335500	40 155-165
180-195	465	6.0	14.3	5.0	1.445	6335690	40 180-195
205-220	465	6.0	14.3	5.0	1.448	6335770	40 205-220

40 Z

HOOK WRENCH with pin

- Acc. to DIN 1810, Form B
- For cross-drilled nuts according to DIN 1816
- GEDORE vanadium steel 31CrV3, manganese-phosphated




mm	L	d	n	t ₂	kg	Code	No.
16-18	110	2.5	3.8	2.5	0.014	6335850	40 Z 16-18
20-22	110	2.5	3.8	2.5	0.014	6335930	40 Z 20-22
25-28	135	3.0	4.5	3.0	0.039	6336580	40 Z 25-28
30-32	135	4.0	4.5	3.0	0.045	6336660	40 Z 30-32
34-36	170	4.0	5.5	3.5	0.080	6336740	40 Z 34-36
40-42	170	4.0	5.5	3.5	0.079	6336820	40 Z 40-42
45-50	205	5.0	6.5	4.0	0.136	6336900	40 Z 45-50
52-55	205	5.0	6.5	4.0	0.129	6337040	40 Z 52-55
58-62	240	5.0	7.5	5.0	0.198	6337120	40 Z 58-62
68-75	240	6.0	7.5	5.0	0.198	6337200	40 Z 68-75
80-90	280	6.0	8.5	6.0	0.281	6337390	40 Z 80-90
95-100	280	8.0	8.5	6.0	0.276	6337470	40 Z 95-100
110-115	335	8.0	10.3	8.0	0.494	6337550	40 Z 110-115
120-130	335	8.0	10.3	8.0	0.492	6337630	40 Z 120-130
135-145	385	8.0	12.3	8.0	0.829	6337710	40 Z 135-145
155-165	385	8.0	12.3	8.0	0.841	6337980	40 Z 155-165
180-195	465	10.0	14.3	8.0	1.420	6338010	40 Z 180-195
205-220	465	10.0	14.3	8.0	1.402	6338280	40 Z 205-220

44

CALIPER FACE SPANNER adjustable

- Similar to DIN 3116
- Special sizes on request
- GEDORE vanadium steel 31CrV3, manganese-phosphated



mm	L	d	t	kg	Code	No.	
3	178	7	2.9	4	0.148	6354480	44 3
4	178	7	3.8	5	0.151	6354560	44 4
5	230	9	4.8	6	0.259	6354640	44 5
6	230	9	5.8	7	0.260	6354720	44 6
8	230	9	7.8	8	0.265	6354990	44 8

PRACTICAL HELPERS

639

COMBINATION HOLDING TOOL

- Small helper to hold nuts and washers in barely accessible places
- For thread sizes from M3 to M8
- Delivery without tools and accessories



L	W	H	kg	Code	No.
110	19.2	9.7	0.016	1640852	639

636

PLUS-FORM HANDLE

- Push-on handle for spanners
- Designed for use with no. 4, 6, 7, 894, 895 sizes 13 - 22 mm
- Where high hand force is needed to turn the spanner, the ergonomic Plus-Form handle distributes the force evenly over the hand
- This avoids painful pressure points in the palm
- The special design of the holder and counter-holder safely secures the spanner in the handle
- Ideal for removing tight bolts
- The Plus-form handle extends short spanners, increasing the applied force!
- Practical hanging hole
- Made from scratch-proof, sky-blue powder-coated sheet steel
- Patent applied
- Delivery without tools



kg	Code	No.
0.100	1999079	636

637

RETAINING CLIP FOR NUTS

- With magnetic holder
- Suitable for open ended and flat ring spanners size 10-19 mm
- Delivery without tools and accessories



kg	Code	No.
0.006	1834150	637