

STRAP WRENCHES

36

STRAP WRENCH

- ▶ With strong, non-slip fabric strap (E-36), extra wide = 25 mm
- ▶ 36 1-140 made from C45 steel
- ▶ 36 2-200 made from GEDORE vanadium steel 31CrV3
- ▶ Chrome-plated



∅ mm	∅ inch	l mm	mm	kg	Code	No.
140	9/64	220	25	0.278	6327320	36 1-140
200	13/64	285	25	0.578	6327400	36 2-200

E-36

STRAP WRENCH

- ▶ Strong, non-slip fabric strap, extra wide = 25 mm



l mm	mm	kg	Code	No.
480	25	0.062	5327380	E-36 1-140
900	25	0.104	5327460	E-36 2-200

36Z

SPECIAL STRAP WRENCH

- ▶ For tightening and counter-holding V-belt pulley wheels
- ▶ Spare strap E-36 Z



l mm	∅ mm	∅ inch	kg	Code	No.
257	160	5/32	0.379	6320070	36 Z-140

E-36 Z

SPARE STRAP

l mm	kg	Code	No.
257	0.080	1380613	E-36 Z-140

126

STRAP WRENCH

- ▶ Very gentle to surfaces, particularly suitable for chrome-plated fittings and polished surfaces
- ▶ Handle in light metal, enamelled blue
- ▶ With high-strength nylon strap



∅ mm	∅ inch	l mm	mm	kg	Code	No.
220	8	300	27	0.325	1468308	126008

E 126

SPARE STRAP

- ▶ High-strength nylon strap



l mm	mm	kg	Code	No.
950	27	0.035	1468316	126208

WATER PUMP / UNIVERSAL PLIERS

142

UNIVERSAL PLIERS

- ▶ Acc. to DIN ISO 8976 Form C
- ▶ With safety box joint and protection against blocking
- ▶ Fine adjustment
- ▶ 142 7 = 17 settings
- ▶ 142 10 = 15 settings
- ▶ 142 12 = 17 settings
- ▶ Single-hand push-button adjustment
- ▶ Long slim jaws
- ▶ Offset gripping faces for self-gripping of nuts and pipes
- ▶ GEDORE special chrome-vanadium steel
- ▶ Induction-rehardened serrated faces
- ▶ Model C = slim handles with forged serrations
- ▶ Model TL = agate-grey, with blue dipped handle protectors
- ▶ Model JC = chrome-plated, 2-component handles



142-10 C



142-10 JC




142-10 TL



142-12 TL



142-12 C



L ₁	L ₂	b	h	mm	kg	Code	No.
180	32	6.5	40	37	0.183	2668211	142 7 TL
180	32	6.5	40	37	0.173	2668238	142 7 C
255	39	7.5	48	38	0.371	6416180	142 10 TL
250	39	7.5	48	38	0.380	6416260	142 10 C
260	39	7.5	48	38	0.417	6416340	142 10 JC
309	43	8.5	55	44	0.550	1995413	142 12 TL
300	43	8.5	55	44	0.530	1995553	142 12 C