

## VDE 4507 VDE TORQUE WRENCH 1/2"



5-50 N·m / 4-37 lbf·ft

- > Controlled screw tightening in the most common range of 5 - 50 N·m / 4 - 37 lbf·ft
- > Automatic short-path actuation with tactile impulse and audible signal
- > Dual scale with a scale graduation of 5 N·m and 5 lbf·ft
- > Fine toothed ratchet with square drive as per DIN 3120 - A 12.5, ISO 1174
- > VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, two-ply Check-Tool insulation




"	mm	mm	kg	Code	No.
1/2	12.5	370	1.251	6681920	VDE 4507-4

## VDE 30 VDE SOCKET 3/8"



- > Hexagon socket wrench, hand-operated
- > With square drive according to DIN 3120 - C 10, ISO 1174
- > GEDORE vanadium steel 31CrV3
- > VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, two-ply Check-Tool insulation
- > 16 - 18 mm insulation overhang



Ø	d <sub>1</sub>	d <sub>2</sub>	L	Code	No.
6	13.7	23	44	2946386	VDE 30 6
8	16.1	23	44	2946394	VDE 30 8
9		23	44	2946408	VDE 30 9
10	18.7	23	44	2946416	VDE 30 10
11	20.0	23	44	2946424	VDE 30 11
12	21.2	23	44	2946432	VDE 30 12
13	22.5	23	44	2946440	VDE 30 13
14	23.7	23	45	2946459	VDE 30 14
15	25.0	23	46	2946467	VDE 30 15
16	26.2	23	46	2946475	VDE 30 16
17	27.5	23	46	2946483	VDE 30 17
18	28.7	23	46	2946491	VDE 30 18
19	30.0	23	46	2946505	VDE 30 19
20	31.2	23	47	2946513	VDE 30 20
22	33.7	23	48	2946521	VDE 30 22

## VDE INX 30 VDE SCREWDRIVER BIT SOCKET 3/8"



for multi-point screws XZN

- > With pressed-in pin
- > With square drive according to DIN 3120 - C 12.5, ISO 1174
- > Bit in GEDORE vanadium special steel, manganese-phosphated
- > VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, two-ply Check-Tool insulation



Code	No.
M8 2946564	VDE INX 30 8
M10 2946572	VDE INX 30 10
M12 2946580	VDE INX 30 12

## VDE 3093 U VDE REVERSIBLE RATCHET 3/8"



with push-button release

- > Robust, with smooth action
- > Sockets held absolutely securely by push-button lock with ball in the square drive
- > Direction changed by 2 push-buttons, marked R and L, on the shaft
- > Return angle 8.2 degrees
- > Square drive acc. to DIN 3120 - A 10, ISO 1174, chrome-vanadium steel 31CrV3
- > VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900



## VDE 3090 VDE EXTENSION 3/8"



- > For hand-operated sockets with square drive as per DIN 3120, ISO 1174
- > VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, two-ply Check-Tool insulation
- > 16 - 18 mm insulation overhang



"	mm	Code	No.
3/8	10	2946548	VDE 3090-3
3/8	10	2946556	VDE 3090-6

"	mm	mm	kg	Code	No.
3/8	10	185	0.215	2946599	VDE 3093 U

