




# ALFRA ROTABEST®-60 RL-E



80 mm

DRILLING RANGE UP TO Ø 80 MM



## Scope of Supply:

- Metal core drilling machine 60 RL-E
- Carrying case
- Coolant equipment
- Drilling spray
- Quick-release chuck, 1 to 16 mm, MT 3
- Chip hook
- Safety belt
- Operating manual

## 60 RL-E

Cutter dimension	Ø 12.0 - 80.0 mm / Ø 20.0 - 50.0 mm (extra long 110 mm)
Cutting depth	50.0 mm / 110.0 mm
Twist drill	Ø 1.0 - 16.0 mm with chuck to Ø 32.0 mm with MT 3 DIN 345
Counterbore	Ø 10 - 55.0 mm
Tapping	with tapping chuck: to M30 with tapping attachment: to M30
Arbor	MT 3
Stroke	190 mm
Height adjustment	60 mm
4-speed gearbox	right/left 1. Gear 50 - 110 rpm. 2. Gear 75 - 175 rpm. 3. Gear 105 - 245 rpm. 4. Gear 165 - 385 rpm.
Power consumption	1.800 W
Voltage	230 V 50/60 Hz / 110 V 50/60 Hz
Tool Force (10 mm) / magnetic holding force	4.200 N / 20.000 N
Magnet foot	80 x 230 mm, 30° adjustable, right and left, 10 mm front and rear
Weight	22.0 kg

<b>Motor</b>	
Full-wave control electronics	✓
Right/left run	✓
<b>Gearbox</b>	
Oil-bath gearbox	✓
Mechanical slipping clutch	✓
<b>Slide</b>	
Stepless adjustment	✓
<b>Operation</b>	
Soft-touch grips	✓
Membrane keyboard	✓
Cord length 5 m	✓
<b>Magnet</b>	
Metal rings	✓
	✓

## Prod.-No.

ALFRA Rotabest® 60 RL-E	230 Volt	18626
ALFRA Rotabest® 60 RL-E	110 Volt	18626.110