




ALFRA ROTABEST®-V32



32
mm

DRILLING RANGE UP TO Ø 32 MM



V32	
Core drill	Ø 12.0 - 32.0 mm
Cutting depth	25.0 mm
Counterbore	Ø 10.0 - 32.0 mm
Arbor	19 mm Weldon
1-speed gearbox	450 rpm.
Power consumption	900 W
Voltage	230 V 50/60 Hz / 110 V 50/60 Hz
Tool Force (10 mm) / magnetic holding force	- / 16.000 N
Magnet foot	95 x 200 mm
Weight	12.5 kg

Motor	
Compact, horizontal	
Gearbox	
Compact mitre gear	
Slide	
2-sided pillar guidance	
Operation	
Space-saving – via ratchet	
Cord length 5 m	✓
Magnet	
Metal rings	✓
Performance and weight optimisation	✓
	✓

Scope of Supply:

- Metal core drilling machine V 32
- Coolant pressure flask
- Carrying case
- Allen key for Weldon shank
- Safety belt
- HSS Co cutter Ø 18 mm, cutting depth 25 mm
- Ejector pin 6.35 x 74 mm (specially for Rotabest® V32)
- Operating manual

Prod.-No.

ALFRA Rotabest® V32	230 Volt	18710
ALFRA Rotabest® V32	110 Volt	18710.110

B