



ALFRA ROTABEST®-130

130
mm



DRILLING RANGE UP TO Ø 130 MM



SICHERHEITSHINWEISE

SAFETY NOTICE

ATTENTION


PRECAUTION

PRECAUTION

PRECAUTION

PRECAUTION

PRECAUTION



130
mm

DRILLING RANGE UP TO Ø 130 MM



Scope of Supply:

- Metal core drilling machine 130
- Carrying case
- Coolant container
- Chip hook
- Safety belt
- Operating manual

130	
Cutter dimension	Ø 12.0 - 130.0 mm / Ø 20.0 - 50.0 mm (extra long 110 mm)
Cutting depth	50.0 mm / 110.0 mm
Twist drill	to Ø 45.0 mm with MT 4 DIN 345
Counterbore	Ø 10.0 - 80.0 mm
Tapping	with tapping attachment: To M42
Arbor	MT 4
Stroke	230 mm
Height adjustment	100 mm
4-speed gearbox	1. Gear 30 - 80 rpm. 2. Gear 50 - 120 rpm. 3. Gear 130 - 350 rpm. 4. Gear 210 - 550 rpm.
Power consumption	2,500 W
Voltage	230 V 50/60 Hz / 110 V 50/60 Hz
Tool Force (10 mm) / magnetic holding force	5,000 N / 32,000 N
Magnet foot	90 x 400 mm
Weight	34.5 kg

Gearbox	
Oil-bath gearbox	✓
Mechanical slipping clutch	✓
Operation	
Soft-touch grips	✓
Membrane keyboard	✓
Cord length 5 m	✓
Magnet	
Metal rings	✓
	✓

Prod.-No.

ALFRA Rotabest® 130	230 Volt	18645
ALFRA Rotabest® 130	110 Volt	18645.110