

Edge clamps

For all edge clamping needs



Complete specialised tasks easily

Special tasks and applications often require the use of special tools. Which is why, for edge clamping,

BESSEY has come up with a series of light, easy-to-handle edge clamps. Also available for one-handed operation if required. Specially developed to make your day-to-day work even easier!

The one-handed edge clamp EKT – ideal for applying multi-layered edge strips with just one hand.

The edge clamp KT8-3 – a C-frame that is robust for heavy duty and high clamping pressures.



Your benefits at a glance:

- 1 Unique twin spindle**
The outer spindle acts on the clamping jaws. The inner spindle applies pressure to the front edge. And the impact resistant plastic handle for one-handed use means that any task or application is well within your grasp.
- 2 Large jaws**
Non-slip, gentle clamping. Max. opening distance: 55 mm. The large jaws with integrated colourless soft plastic caps increase the versatility of the clamp.
- 3 Swivel pressure plate**
The large pressure plate will swivel to apply pressure wherever it is required.
- 4 Light aluminium housing**
Lightweight yet highly effective. The statically-optimised aluminium housing creates a corrosion-resistant body for the convenient, one-handed edge clamp EKT.



One-handed edge clamp EKT



N ^o	← a →	← b →	⚖	📦	
	mm	mm	kg	qty.	VB0003
EKT55	10-55	45	0.82	1	

- For rapid one-handed operation
- Low weight
- Opening up to 55 mm



Edge clamp Kantenfix KF



N ^o	← a →	← b →	⚖	📦	
	mm	mm	kg	qty.	VB0003
KF2	10-40	80	0.76	10	
KF4	10-80	110	1.58	1	



- For quick one-handed operation
- Widths up to 80 mm

Edge clamps



- Practical accessory for clamping edges and difficult to reach areas
- Suitable for conventional screw clamps with a max. rail thickness of 13 mm



Edge clamp KT

№	Description	For rail thickness up to max.	⚖	📦	VB0001
		mm	kg	qty.	
KT5-1CP	1 spindle	13	0.35	1	
KT5-2	2 spindles	13	0.58	1	

- Three-spindle C-frame clamp
- Extra strong, with forged frame
- Universally applicable within the fields of wood and metal processing
- Suitable for welding



C-frame edge clamp KT

№	< a >	< b >	⚖	📦	VB0003
	mm	mm	kg	qty.	
KT8-3	0 - 80	80	2.37	5	

- Double-spindle C-screw clamp
- High pressure for gluing edges
- Arm made from malleable cast iron



Edge clamp CKT

№	< a >	< b >	⚖	📦	VB0003
	mm	mm	kg	qty.	
CKT7-6	20-70	60	1.57	10	



Panel carrier KFP

№	< a >	⚖	📦	VB0003
	mm	kg	qty.	
KFP	10-65	1.01	2	

- Load-bearing capacity 75 kg
- For the safe lifting and carrying of panels such as wood sheets, chipboard panels, glass and plexiglass
- High-friction rubber coating on the moving clamping jaws