


# WATERPUMP PLIERS

88

## KNIPEX Alligator® Water Pump Pliers

DIN ISO 8976



88 01 180  




88 01 250  




88 02 250  




88 03 250  




88 04 250  




88 07 250  




More output and comfort compared to conventional water pump pliers of the same length: 9-notch adjustment positioning for 30 % more gripping capacity; good access to the workpiece due to slim size in the head and joint area.


- self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: low wear and stable gripping
- box-joint design: high stability because of the double guide
- robust construction, insensitive to dirt; particularly suitable for outdoor work
- guard prevents operators' fingers being pinched
- Chrome vanadium electric steel, forged, oil-hardened

### 88 02 250 / 88 05 250

with slim multi-component grips without collar for better handling and easier transport



Self-locking on pipes and nuts: no slipping on the workpiece; the complete actuating force can be used to turn the workpieces; not having to squeeze the pliers handles reduces the required effort





# Alligator®



Conventional water pump pliers

Alligator® 250/300



**specially hardened teeth**  
high resistance to wear, allowing durable, reliable gripping

**robust adjusting mechanism**  
insensitive to dirt, particularly suitable for outdoor work

**9-notch curved adjustment positioning**  
30 % more gripping capacity, optimised adjustment to the workpiece and a handy handle position, slim design

**box joint, double guide**  
no loosening of the joint connection, continuous heavy duty

Article No.	EAN 4003773-	↔ mm		Pliers	Head	Handles	∅ Inch	∅ mm	∅ mm	Adjustment positions	g
88 01 180	035480	180		black	polished	with non-slip plastic coating	1 1/2	42	36	9	180
88 01 250	022992	250		atramentized	polished	with non-slip plastic coating	2	50	46	9	319
88 01 300	034094	300					2 3/4	70	60	9	511
88 02 180	044222	180		black	polished	with multi-component grips	1 1/2	42	36	9	215
88 02 250	019282	250		atramentized	polished	with multi-component grips	2	50	46	9	357
88 02 300	029151	300					2 3/4	70	60	9	565
88 03 180	042860	180		chrome plated		with non-slip plastic coating	1 1/2	42	36	9	181
88 03 250	005742	250		chrome plated		with non-slip plastic coating	2	50	46	9	317
88 05 180	060130	180		chrome plated		with multi-component grips	1 1/2	42	36	9	214
88 05 250	035497	250		chrome plated		with multi-component grips	2	50	46	9	354
88 05 300	042389	300					2 3/4	70	60	9	560
88 06 250	039303	250	 	chrome plated		insulated with multi-component grips, VDE-tested	2	50	46	9	374
88 07 250	019343	250	 	chrome plated		with dipped insulation, VDE-tested	2	50	46	9	420
88 07 300	022350	300	 	chrome plated		with dipped insulation, VDE-tested	2 3/4	70	60	9	661

