

# WIRE STRIPPERS

12  
64

## Automatic Insulation Stripper for flat cable



12 64 180  


- for PVC insulated flat cables up to a max. 12 mm width and 0.75 to 2.5 mm<sup>2</sup>
- adapts automatically to the various conductor heights; prevents damage to the conductor
- long stripping lengths possible
- blade replaceable
- smoothly operating mechanism
- low weight
- Body: plastic, fibreglass-reinforced
- Blade: special tool steel, oil-hardened



Article No.	EAN 4003773-	↔ mm	Stripping capacities mm <sup>2</sup>	AWG	g
12 64 180	073284	180	 0.75 - 2.5	19 - 13	125

12  
80

## Mini Stripping Tool



12 80 100 SB  


- precise stripping, stepwise adjustment to the conductor diameters
- with wire cutter
- adjustable length stop from 4.0 - 15.0 mm
- with locking device
- Housing: plastic, impact-proof

### 12 80 040 SB

for thin copper conductors  
dia. 0.12 to 0.4 mm

### 12 80 100 SB

for thin copper conductors  
dia. 0.3 to 1.0 mm



Article No.	EAN 4003773-	↔ mm	Stripping capacities Ø mm	AWG	g
12 80 040 SB	071655	100	0.12 - 0.4	36 - 26	52
12 80 100 SB	043119	100	0.30 - 1.0	28 - 18	34

12  
82

## Wire Stripper for fibre optics



12 82 130 SB

- to remove primary and secondary coating of fibre optics
- Chrome vanadium electric steel in special quality, oil-hardened



Article No.	EAN 4003773-	↔ mm	Pliers	Handles	Stripping capacities Ø mm	g
12 82 130 SB	050094	130	burnished	with plastic grips	primary-coating: 0.125 mm / secondary-coating: 0.250 mm	69